



WA30 OWNERS MANUAL



2 YEAR LIMITED WARRANTY

Washburn electronics and speaker enclosures are warranted to be free of defects in materials and workmanship in normal use for a period of three (2) years from the date of original purchase. During that period, Washburn will, at its option, repair or replace materials at no charge. Products must be delivered to Washburn Feight pre paid by a Washburn Dealer or to an authorized Washburn service center with the original sales receipt or other proof of purchase. Warranty excludes exterior finish, normal wear and tear, failure due to abuse or operation outside the specified ratings. Warranty applies to original purchaser only. Warranty gives you specific rights which vary from state to state. For more information regarding warranty or service please contact:

Washburn Customer Service 444 East Courtland St. Mundelein, IL 60060 USA 847-949-0444

RETAIN FOR YOUR RECORDS

(Complete, detach and return to	٧	Vashburn within	10) (days of	f purch	nase)	ļ
---------------------------------	---	-----------------	----	-----	---------	---------	-------	---

□ Price □ Sound □ Appearance □ Dealer's Presentation □ Catalog and Specifications

HOW WILL THIS WASHBURN PRODUCT BE USED?:

□ Sound Reinforcement / PA □ Band Sound System □ Permanent Installation □ DJ System

WHAT OTHER COMPONENTS WILL BE USED WITH THIS WASHBURN PRODUCT?:

Foreword

Thank you for purchasing the Washburn WA30 acoustic guitar amplifier. Read this manual thoroughly prior to using your amplifier in order to get the most out of the functions available. Ensure that this manual is also stored in a safe place.


Features

The WA30 amplifier provides 30W of output and is mounted with a 10-inch woofer and tweeter. The pre-amp is equipped with vocal guitar inputs. The EQ employs bass and treble and a variable parametric EQ in the middle to produce a wide range of sound. Moreover, the speed of the chorus effect (turned ON/OFF by switch) can be controlled. The WA30 is also equipped with a built-in variable level reverberation function to bring out the depth of sound. Reverberation comes in with the microphone pre-amp but does not come in with the EQ or chorus, so the sound quality remains constant, while the sound characteristics of the guitar can be controlled.


Precautions During Use

- Do not subject the amplifier to shocks by dropping or rough handling.
- Install the amplifier in a stable location. The amplifier will sound differently depending on the method, location, or venue of installation.
- Ensure that the power supply is switched OFF when the amplifier is not in use. Also remove the power cable from the power supply socket when the amplifier is not to be used for an extended period of time.
- Do not use or store the amplifier in locations where it is subject to direct sunlight or in environments that experience dramatic flustrations in temperature and humidity locales
- fluctuations in temperature and humidity levels.
 Reduce the volume to "0" or switch OFF the power supply when connecting the guitar shielded cable, the microphone cable, and cables connected to external units, such as the effects. Note that the noise generated when plugs are inserted or removed may cause severe damage to equipment.


SAMPLES



Strumming



Arpeggio



SPECIFICATIONS

Chorus

OUTPUT POWER: 30W (at 1KHz/8ohms) POWER CONSUMPTION: 34W

INPUT SENSITIVITY: 34W
S/N: 2.2 Mohms
-46dB

CONTROLS: MICROPHONE VOLUME GUITAR VOLUME

GUITAR VOLUME CHORUS SPEED BASS

BASS $(75Hz) \pm 15dB$ MIDDLE FREQ. $400Hz \sim 2KHz$ MIDDLE LEVEL $\pm 15dB$ TREBLE $(5.6KHz) \pm 15dB$

SWITCHES: POWER ON/OFF CHORUS ON/OFF

JACKS: MICROPHONE INPUT 1/4" STEREO

MICROPHONE INPUT XLR

GUITAR INPUT

SPEAKER UNITS: POWER JAM PJ30A 30W RMS (60W PEAK)

APPLY FIRST CLASS POSTAGE





USA